

IN THE U.S. PATENT AND TRADEMARK OFFICE  
Patent Application Transmittal Letter

ASSISTANT COMMISSIONER FOR PATENTS  
Washington, D.C. 20231

Sir:

Transmitted herewith for filing under 37 CFR 1.53(b) is a(n): ☒ Utility ☐ Design

☒ original patent application,

☐ continuation-in-part application

INVENTOR(S): Qiming Chen et al

TITLE: OLAP-Based Customer Behavior Profiling Method And System

Enclosed are:

- ☒ The Declaration and Power of Attorney. ☒ signed ☐ unsigned or partially signed  
☒ 4 sheets of drawings (one set) ☐ Associate Power of Attorney  
☐ Form PTO-1449 ☐ Information Disclosure Statement and Form PTO-1449  
☐ Priority document(s) ☐ (Other) \_\_\_\_\_ (fee \$ \_\_\_\_\_)

CLAIMS AS FILED BY OTHER THAN A SMALL ENTITY				
(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) TOTALS
TOTAL CLAIMS	26 — 20	6	X \$18	\$ 108
INDEPENDENT CLAIMS	3 — 3	0	X \$78	\$ 0
ANY MULTIPLE DEPENDENT CLAIMS	0		\$260	\$ 0
BASIC FEE: Design \$310.00 ); Utility \$690.00 )				\$ 690
TOTAL FILING FEE				\$ 798
OTHER FEES				\$
TOTAL CHARGES TO DEPOSIT ACCOUNT				\$ 798

Charge \$ 798 to Deposit Account 08-2025. At any time during the pendency of this application, please charge any fees required or credit any over payment to Deposit Account 08-2025 pursuant to 37 CFR 1.25. Additionally please charge any fees to Deposit Account 08-2025 under 37 CFR 1.16, 1.17, 1.19, 1.20 and 1.21. A duplicate copy of this sheet is enclosed.

"Express Mail" label no. EL 519 583 576 US

Date of Deposit March 10, 2000

I hereby certify that this is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231.

By Noli Dumlaog

Typed Name: Noli Dumlaog

Respectfully submitted,

Qiming Chen et al

By

Thomas X Li

Attorney/Agent for Applicant(s)

Reg. No. 37,079

Date: March 10, 2000

Telephone No.: (650) 857-5972

United States Patent Application  
for

OLAP-Based Customer Behavior Profiling Method and System

Inventors:

Qiming Chen  
Umeshwar Dayal  
Meichun Hsu

EXPRESS MAIL CERTIFICATE OF MAILING

"Express Mail" mailing label number: 51 519 583 576 45

Date of Deposit: March 10, 2000

I hereby certify that I am causing this paper or fee to be deposited with the United States Postal Service "Express Mail Post Office to Addressee" service on the date indicated above and that this paper or fee has been addressed to the Assistant Commissioner for Patents, Washington, D. C. 20231

NOLI DUMLAO  
(Typed or printed name of person mailing paper or fee)

Noli Dumlaos  
(Signature of person mailing paper or fee)

OLAP-BASED CUSTOMER BEHAVIOR PROFILING METHOD AND SYSTEMField of the invention

5           The present invention relates generally to data processing and more specifically to an OLAP-based customer behavior profiling method and system.

Background of the Invention

10           Telecommunication fraud is a major problem that costs the telephone service providers many millions of dollars annually. There are generally two types of telecommunication fraud: fake identity and real identity fraud. In fake identity fraud, the impostor uses another's access code to access telephone services (e.g., local or long distance access). In a real identity fraud, the perpetrator uses a real identity, but fails to pay the telephone service providers for services. When the telephone company stops providing service to a real identity fraud perpetrator, the perpetrator either applies for a new number or switches service providers, thereby continuing to defraud the telephone service providers.

15           To counteract these problems, telephone service providers currently hire consultants and provide them with past calling records, which typically include all the calling records for a previous year. The consultants then take six months or more to sort through the many millions of records and to generate a report that describes any suspicious activity for the past year. Unfortunately, the prior art tools for fraud detection utilized by the consultants to analyze the records are very limited and employ very crude or coarse threshold detection methods to detect the fraudulent behavior.

20           For example, one prior art threshold detection method is based solely on the length of the telephone call. When a particular call exceeds a particular length (e.g., 24 hours), the method informs the consultant that the call is probably fraudulent. Another prior art threshold detection method is based on both the length of the call and the time when the call occurred. When a particular call is more than a particular length of time (e.g., 4 hours), and the call occurs in the evening (e.g., after 10PM), then this prior art method classifies the call as "fraudulent."

These current methods suffer from several disadvantages. First, these tools do not have the ability to generate a specific and personalized caller profile and to use that profile to detect suspicious calling activity that corresponds to a unique calling behavior. As noted, only very coarse threshold can be established. Personalized profiles are important because calling behavior that may considered to be abnormal calling behavior (e.g., phone calls in the evening that last more than four hours) for a first caller, who normally makes no calls in the evenings, may be normal activity for a second caller, who only makes calls in the evenings that average between five and six hours. Thus, it is desirable to have a mechanism that can establish a personalized threshold or baseline that differs among different callers thereby accommodating different callers, who inevitably have different calling behaviors and patterns. Such a mechanism could then determine what is abnormal calling activity as measure to a baseline of that caller's previous calling behavior.

Second, the prior art approaches consume much time. Because of the time needed by the consultants to perform the analysis and generate the report, the impostor or perpetrator of telephone fraud will more than likely have moved onto a different telephone service provider or to new telephone number by the time any fraud has been detected. In addition, there will always be six months to a year or more of unrecoverable profits lost to fraudulent behavior before that behavior is detected, if at all. It is desirable to have a mechanism that reduces the time needed between the fraudulent activity and the detection thereof.

Third, the prior art methods are also poor at handling the volume of calls. Even if more consultants were hired, and these consultants worked around the clock, they would be unable to handle the sheer volume of calls that are continuously generated. The volume of call data is in the order of millions of call records per day for a particular local geographic area. It is desirable to have a mechanism that can incrementally update an existing profile to reflect information from the new call records.

Furthermore, the prior art methods are limited to analyzing past calling records and are unable to provide up-to-date reports that reflect current call records and trends. In this regard, it is desirable to develop a system that is scaleable (i.e., that can automatically process new records

on a periodic basis and generate reports that reflect new information provided by the new records).

Fourth, these prior art methods use volume data, which is difficult to compare across different time periods. For example, the number of calls made in a single month (e.g., January) cannot be compared to the total number of calls made for an entire year (e.g., 1999). Similarly, a weekly measure of the number of calls made by a particular caller makes cannot be compared to a monthly measure of the number of calls made by the same caller. In the example given above, suppose the consultant studies the past six months of call records and determines that it is likely that any caller who makes more than 100 calls for a duration of more than 24 hours in six months is likely to be fraudulent. This information is not useful for determining if a caller over a time frame different from six months is perpetrating telephone fraud. In addition, It is desirable instead to have a mechanism that generates values that can be compared easily across different time periods.

Accordingly, there remains a need for a method for generating and using caller profiles to detect telecommunication fraud that overcomes the disadvantages set forth previously.

SUMMARY OF THE INVENTION

The present invention discloses an OLAP-based method and system for profiling customer behavior. In one embodiment, the present invention is applied to telecommunication fraud detection and involves processing call records. In this embodiment, the following steps are performed. First, call records are received. Next, a calling profile cube (e.g., a multi-customer profile cube) is generated based on the call records. A volume-based calling pattern cube (e.g., a calling pattern cube for each individual customer) is then generated based on the multi-customer profile cube. The volume-based calling pattern cube is then compared with known fraudulent volume-based calling patterns. If the similarities generated by the comparison reaches or exceeds a predetermined threshold, then the particular caller with the calling pattern being analyzed is considered suspicious. In this manner, suspicious calling activity can be detected, and appropriate remedial actions, such as further investigation or the cancellation of telephone services, can be taken.

In an alternative embodiment, after the volume-based calling pattern cube (e.g., a calling pattern cube for each individual customer) has been generated, a probability-based calling pattern cube is generated based on the volume-based calling pattern cube. The probability-based calling pattern is then compared with known probability-based fraudulent patterns. If the similarities generated by the comparison reaches or exceeds a predetermined threshold, then the particular caller with the calling pattern being analyzed is considered suspicious. One advantage of the alternative embodiment over the first embodiment described above is that two patterns that cover different time periods can be compared and analyzed.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram illustrating a data processing system configured in accordance with one embodiment of the present invention.

FIG. 2 is block diagram illustrating in greater detail the OLAP server of FIG. 1.

FIG. 3 is a flowchart illustrating the operation of the OLAP-based profile engine of FIG. 2 according to one embodiment of the present invention.

FIG. 4 illustrates exemplary volume and probability based calling patterns that can be generated by the profile engine of the present invention.

DETAILED DESCRIPTION

The subject invention will be described with reference to numerous details set forth below, and the accompanying drawings will illustrate the invention. The following description and the drawings are illustrative of the invention and are not to be construed as limiting the invention. Numerous specific details are described to provide a thorough understanding of the present invention. However, in certain instances, well-known or conventional details are not described in order not to obscure unnecessarily the present invention in detail. In the drawings, the same element is labeled with the same reference numeral.

One aspect of the present invention is the use of an OLAP-based profile engine as a scalable computation engine to compute, maintain and utilize customer behavior profiles. In other words, the present invention provides an OLAP-based system and method for customer behavior profiling and pattern analysis that powerfully extends the limited capabilities of traditional OLAP tools that were generally directed only to query and analysis of data.

Another aspect of the present invention is to generate personalized or group-based thresholds that are more precise and useful than generalized thresholds of the prior art. For example, by generating personalized calling behavior profiles, the present invention can determine that calls by John for four hours are considered usual, but calls by Jane for two hours are considered unusual.

Yet another aspect of the present invention is the use of an OLAP-based method and system to detect telephone fraud by comparing a known fraudulent profile to customer profile. For example, in one embodiment, the present invention profiles each new customer's calling behavior and compares these profiles against known fraudulent profiles to detect fraud.

According to yet another aspect of the present invention, profiles and calling patterns are represented as multi-level and multidimensional cubes.

In one embodiment of the present invention, profiles and calling patterns are based on the probability distribution of call volumes. The present invention can utilize an OLAP-based profile engine to compute these probability distributions.

The architecture of a data processing system configured in accordance with one embodiment of the present invention is illustrated in FIG. 1, and an OLAP-based profiling



engine that is configured in accordance with one embodiment of the present invention is illustrated in FIG. 2. A flowchart of the method of generating and using calling patterns for fraud detection is illustrated in FIG. 3. Profiling with fixed values and probability distributions are described with reference to TABLE 1 and TABLE 2, respectively. Volume and probability based calling patterns are described with reference to FIG. 4.

#### OLAP-Based Data Processing System 100

One substantial challenge for the prior art approaches to caller fraud detection is how to process the sheer volume of call data in order to generate caller profiles and update them. In order to create and update customer behavior profiles, hundreds of millions of call records must be processed everyday.

The present invention overcomes this challenge by providing an OLAP-based architecture or framework that is both scalable and maintainable to support customer behavior profiling. One application of the OLAP-based architecture of the present invention is caller behavior profiling for telecommunication fraud detection.

FIG. 1 is a block diagram illustrating a data processing system 100 configured in accordance with one embodiment of the present invention. The data processing system 100 includes a data warehouse 104, an OLAP server 108 that has a profile engine 152, and a multi-dimensional database 120. The present invention powerfully extends the function of a traditional OLAP server 108 by providing the profile engine 152. In the preferred embodiment, the profile engine 152 of the present invention is an OLAP-based profile engine. As will be described in greater detail hereinafter with reference to FIG. 2, the OLAP-based profile engine 152 of the present invention provides a scalable computation engine for delivering powerful solutions for customer behavior profiling, pattern generation, analysis and comparison, and data management.

First, profiling engine 152 builds and incrementally updates customer calling behavior profiles by mining call records 118 flowing into the data-warehouse 104 on a periodic basis. Second, the profiling engine 152 maintains profiles by staging data between the data-warehouse 104 and an OLAP multidimensional database 120. For example, a profile cube 130, a profile snapshot cube 134, and an updated profile cube 138 (which are part of the OLAP multidimensional database 120) can be generated based on data received from the profile table

110 and the call records table 114. The profile cube 130, the profile snapshot cube 134, and the updated profile cube 138 are described in greater detail hereinafter. Third, the profiling engine 152 derives multilevel and multidimensional customer calling patterns (e.g., calling pattern cubes 140 of individual customers) from the updated profile cube 138 for fraud detection analysis. Fourth, the profiling engine 152 compares the calling patterns with known fraudulent patterns for fraud detection purposes.

The data warehouse 104 includes a profile table 110 for the storing customer profile information and a call record table 114 for storing the call data records (CDRs). For example, call data records (CDRs) 118 may be loaded into the call record table 114 on a periodic basis (e.g., on a daily basis).

In one embodiment, the data warehouse 104 can be implemented with an Oracle-8 based telecommunication data-warehouse, and the OLAP server 108 and multi-dimensional database 120 can be implemented with an Oracle Express multidimensional OLAP server. The profile engine 152 is preferably implemented by OLAP programming (i.e., by a program written in a scripting language provided by the OLAP server 108).

FIG. 2 is block diagram illustrating in greater detail the OLAP server 108 of FIG. 1. The OLAP server 108 includes traditional OLAP analysis and visualization tools 150 that are typically used for query and analysis of corporate data, such as sales, marketing, financial, manufacturing, or human resources data. The OLAP server 108 also includes the profile engine 152, which in accordance to one embodiment of the present invention, is an OLAP-based scalable computation engine for creating profiles, updating profiles, deriving calling patterns from profiles, and analyzing and comparing the calling patterns.

The profile engine 152 includes a profile builder and update module (PBUM) 154, a behavior pattern generation module (BPGM) 158, a data management module (DMM) 160, a volume-based to probability-based conversion module (VPCM) 164, and a behavior pattern comparison module (BPCM) 168.

The profile builder and update module (PBUM) 154 builds and updates customer calling profiles by incrementally mining the CDRs that flow periodically into the data-warehouse 104. Mining refers generally to the well-known process of converting data in a first format (e.g., a

record format suited for a relational database) into a second format (e.g., a multi-dimensional cube format suited for a multi-dimensional database).

The behavior pattern generation module (BPGM) 158 derives customer behavior patterns (e.g., calling pattern cubes) from the customer profiles. The volume-based to probability-based conversion module (VPCM) 164 converts volume-based calling patterns into probability based calling patterns. The behavior pattern comparison module (BPCM) 168 analyzes the calling patterns and compares the calling patterns with personalized profiles or known fraudulent patterns to detect telephone fraud. For example, the BPCM 168 can determine whether a particular customer calling pattern matches with a predetermined profile that is known to be fraudulent and automatically generate an alert if there is a match.

Below is the Oracle-8 schema of the profile table called "Profile", where "pc" is the number of calls dimensioned by other attributes.

```
// Oracle8 table schema
CREATE TABLE Profile
(
    caller          VARCHAR2(10)          NOT NULL,
    callee          VARCHAR2(10)          NOT NULL,
    duration        CHAR(1)               NOT NULL,
    time            CHAR(1)               NOT NULL,
    dow             char(1)               NOT NULL,
    pc              INTEGER               NOT NULL,
)
STORAGE ...;
```

The corresponding profile cube (PC) 130 can be defined in Oracle Express as follows:

```
// Oracle Express cube definition
define PC variable int <sparse <duration time dow callee caller>> inplace
```

where *dow* stands for day\_of\_week (e.g. Monday, ..., Sunday).

It can be seen that the attributes of the profile table 110 has one-to-one correspondence to the dimensions (including the output dimension) of the profile cube 130. The present invention provides this arrangement in order to simplify data staging operations.

Referring to FIG. 3, the steps performed by the profile engine 152 illustrated in FIGS. 1 and 2 are now described. In step 300, the profile builder and update module 154 retrieves a profile table (e.g., profile table 110) from a source (e.g., the data warehouse 104) and provided to a profiling engine 152. In step 304, the PBGM 154 uses the retrieved profile table 110 to automatically generate a profile cube (e.g., profile cube 130). The profile cube 130 can be a multi-level, multi-dimensional, and multi-customer cube and can be generated by utilizing

OLAP programming. In step 308, the PBGM 154 retrieves a call data table (e.g., call data table 114). In step 312, the PBGM 154 uses the retrieved call data table to create a profile-snapshot cube (e.g., profile-snapshot cube 134). The profile snapshot cube 134 can be a multi-level, multi-dimensional, and multi-customer cube and can be generated by utilizing OLAP programming.

5 In step 316, the PBGM 154 merges the profile-snapshot cube 134 and the profile cube 130 to generate an updated profile cube (e.g., updated profile cube 138). Since profile-snapshot cubes 134 and profile cubes 130 have the same dimensions, with cell values representing number of calls, the profile-snapshot cube 134 and a profile cube, 130 covering the same group of callers, can be easily merged by addition. In step 318, the BPGM 158 generates (e.g., derives)  
10 a plurality of individual customer based calling pattern cubes (e.g., calling pattern cubes 140) from the updated profile cube 138. Various kinds of pattern cubes can defined. These pattern cubes 140 can be multi-level and multi-dimensional and can be generated by utilizing OLAP programming. By rolling up these cubes, multilevel calling patterns can be supported. An exemplary method for generating these calling pattern cubes 140 is described in greater detail  
15 herein after.

In step 320, the BPCM 168 analyzes the individual calling patterns in multiple dimensions and at multiple levels. For example, for fraud detection purposes, the BPCM 168 can compare the current calling pattern of a customer for a recent period of time to a baseline established by the calling pattern of the customer during a fixed, predetermined time in the past  
20 (e.g., typical past usage that is personalized). When the differences between these two patterns that reach or exceed a predetermined threshold, the BPCM 168 can automatically generate an alert. Alternatively, a known fraudulent calling pattern can be compared to a plurality of customer patterns. If there is a match, as defined by a predetermined standard, the BPCM 168 can automatically generate an alert.

#### Data Management

25 The data management module 160 handles data staging between the data-warehouse 104 and an OLAP multidimensional database 120. The following steps are repeated periodically (e.g. on a daily basis). First, call data records 118 are loaded into the call data table 114 in the

data-warehouse 104, and then loaded to the profiling engine 152 to generate the profile-snapshot cube 134 that is multi-customer oriented. Second, the profile cube 130 that covers the same set of customers is retrieved from the data-warehouse 104. The step of retrieving the profile cube 130 can occur in parallel with the step of generating the profile-snapshot cube 134. Third, the profile cube 130 is updated to generate the updated profile cube 138 by merging the profile cube 130 with the profile-snapshot cube 134. The updated profile cube 138 can be stored back to the profile table 110 in the data-warehouse 114. The frequency of data exchange between the data-warehouse 104 and the OLAP server 108 can be controlled by predetermined data staging policies. The staging policies can depend on factors, such as, (1) the amount of data flowing into the data warehouse 104; (2) the amount of storage space available in both the data warehouse and the multi-dimensional database 120, and (3) other application-specific criteria.

In order to reduce data redundancy and query cost, it is preferable for the present invention to maintain minimal data in the profile tables 110 in the data-warehouse 104. Accordingly, the present invention stores multiple customers calling information in a single profile table 110 or profile cube 130 without separating information for outgoing calls and incoming calls. The present invention ensures that the relational schema of the profile table 110 directly corresponds to the base level of the profile cube 130. In addition, the present invention does not maintain derivable values at higher levels in the data-warehouse 104.

#### Calling Cubes

In one embodiment, the present invention generates and uses two types of calling cubes: (1) multi-customer based profile cubes (e.g., updated profile cube 138), and (2) single customer based calling pattern cubes 140.

#### Profile Cubes

A profile cube (e.g., profile cube 130) has the same underlying dimensions as a profile-snapshot cube (e.g., profile snapshot cube 134). In addition, the profile cubes and profile snapshot cubes both contain profiling information of multiple customers in direct correspondence with the relational tables (e.g., tables 110 and 114) in the data-warehouse 104. In

one embodiment, the PBUM 154 defines the profile cube and the profile-snapshot cube as follows by utilizing the Oracle Express language:

```
define PC variable int <sparse <duration time dow callee caller>> inplace
define PCS variable int <sparse <duration time dow callee caller>> inplace
```

where callee is the telephone number of the person being called; caller is the telephone number of the person placing the call; dimension *time* has values representing time-bins (e.g., ‘morning’, ‘afternoon’, and ‘evening’); dimension *duration* has values representing duration-bins (e.g., ‘short’, ‘medium’, and ‘long’); and dimension *dow* has values representing days of week (e.g., ‘MON’, .. ‘SUN’).

It is noted that the use of keyword “sparse” in the above definitions instructs Oracle Express to create a composite dimension *<duration time dow callee caller>*, in order to handle sparseness, particularly between calling and called numbers, in an efficient way. A composite dimension is a list of dimension-value combinations. A combination is an index into one or more sparse data cubes. The present invention uses a composite dimension to store sparse data in a compact form similar to relation tuples.

The PBUM 154 populates the profile-snapshot cube PCS by utilizing a mapping process, which is referred to herein as “binning.” Specifically, the PBUM 154 maps the values in the fields of a call data record contains to each dimension of the PCS cube. For example, ‘8am’ is mapped to time-bin ‘morning’, 5 minutes is mapped to duration-bin ‘short’. A call made at 8am and lasting 5 minutes falls into the cell corresponding to *time* = ‘morning’ and *duration* = ‘short’.

The PBUM 154 also retrieves information from the profile table 110 of the data warehouse 104 and represents the retrieved information as profile cube PC and merges the profile cube PC with the PCS cube to generate an updated PC cube, which can be stored back to the data warehouse 104 by the DMM 160. In Oracle Express, the merge of PC and PCS may be expressed as

$$PC = PC + PCS$$

In this manner, the PBUM 154 updates the customer profiles incrementally as each new batch of call data records flows into the data-warehouse.

#### Hierarchical Dimensions for Multilevel Pattern Representation

A hierarchical dimension  $D$  contains values at different levels of abstraction. The following is associated with the hierarchical dimension  $D$ : 1) dimension  $DL$  that describes the levels of the hierarchical dimension  $D$ ; 2) a relation  $DL\_D$  that maps each value of the hierarchical dimension  $D$  to the appropriate level; and 3) a relation  $D\_D$  that maps each value of the hierarchical dimension  $D$  to its parent value (i.e., the value at the immediate upper level). Let  $D$  be an underlying dimension of a numerical cube  $C$ , such as a volume-based calling pattern cube.  $D$ , together with  $DL$ ,  $DL\_D$  and  $D\_D$ , fully specify a dimension hierarchy. They provide sufficient information to rollup cube  $C$  along dimension  $D$ , (i.e., to calculate the total of cube data at the upper levels using the corresponding lower-level data). As can be appreciated, the cube  $C$  can be rolled up along multiple underlying dimensions.

The BPGM 158 generates calling pattern cubes based on the profile cubes. These calling pattern cubes are used to represent the calling behavior of individual customers. The BPGM 158 may employ the dimensions described herein below as hierarchical dimensions in order to represent the calling behavior of individuals at multiple levels. It is noted that the calling pattern cubes can be rolled up along these hierarchical dimensions.

#### Dow Hierarchical Dimension

In accordance with one embodiment of the present invention, the Day of Week (dow) hierarchy includes the following objects:

- *dow*(day of week): dimension with values 'MON', ... 'SUN' at the lowest level (dd level), 'wkday', 'wkend' at a higher level (ww level), and 'week' at the top level ('week' level);
- *dowLevel*: dimension with values 'dd', 'ww', 'week';
- *dow\_dow*: relation (dow, dow) for mapping each value to its parent value, e.g.,  
 $dow\_dow(dow\ 'MON') = 'wkday'$   
...  
 $dow\_dow(dow\ 'SAT') = 'wkend'$   
 $dow\_dow(dow\ 'wkday') = 'week'$   
 $dow\_dow(dow\ 'wkend') = 'week'$   
 $dow\_dow(dow\ 'week') = NA$ ;
- *dowLevel\_dow*: relation (dow, dowLevel) for mapping each value to its level, e.g.,  
 $dowLevel\_dow(dow\ 'MON') = 'dd'$   
...  
 $dowLevel\_dow(dow\ 'wkday') = 'ww'$   
 $dowLevel\_dow(dow\ 'wkend') = 'ww'$   
 $dowLevel\_dow(dow\ 'week') = 'week'$ .

Time Hierarchical Dimension

In accordance with one embodiment of the present invention, the time hierarchy includes the following objects:

- *time*: dimension with values 'night', 'morning', 'afternoon' and 'evening' at 'time\_bin' level (bottom-level), and 'allday' at the 'time\_all' level (top-level);
- *timeLevel*: dimension with values 'time\_bin' and 'time\_all';
- *time\_time*: relation (time, time) for mapping each value to its parent value, e.g.,  
 $\text{time\_time}(\text{time 'morning'}) = \text{'allday'}$   
...  
 $\text{time\_time}(\text{time 'allday'}) = \text{NA}$ ;
- *timeLevel\_time*: relation (time, timeLevel) for mapping each value to its level, e.g.,  
 $\text{timeLevel\_time}(\text{time 'morning'}) = \text{'time\_bin'}$   
 $\text{timeLevel\_time}(\text{time 'allday'}) = \text{'time\_all'}$ .

Duration Hierarchical Dimension

In accordance with one embodiment of the present invention, the duration hierarchy includes the following objects.

- *duration*: dimension with values 'short', 'medium', 'long' at 'dur\_bin' level (bottom-level), and 'all' and 'dur\_all' level (top-level)
- *durLevel*: dimension with values 'dur\_bin' and 'dur\_all'
- *dur\_dur*: relation (duration, duration) for mapping each value to its parent value, e.g.,  
 $\text{dur\_dur}(\text{duration 'short'}) = \text{'all'}$   
...  
 $\text{dur\_dur}(\text{duration 'all'}) = \text{NA}$
- *durLevel\_dur*: relation (duration, durLevel) for mapping each value to its level, e.g.,  
 $\text{durLevel\_dur}(\text{duration 'short'}) = \text{'dur\_bin'}$   
...  
 $\text{durLevel\_dur}(\text{duration 'all'}) = \text{'dur\_all'}$

When the present invention performs profile storage, combination and updating, only the bottom levels are involved. Thus, rolling up profile cubes, such as PC, is unnecessary. It is noted that the present invention applies the roll up operation to calling pattern cubes for analysis purposes.

Volume Based Calling Patterns

In the preferred embodiment of the present invention, a calling pattern cube is associated with a single customer for representing the individual calling behavior of that customer. Since the calling behavior of a customer can be viewed from different aspects, the present invention can define different kinds of calling pattern cubes. These cubes are commonly dimensioned by



*time*, *duration* and *dow* (day of week). Cubes that are related to outgoing calls are commonly dimensioned by *callee*, and cubes that are related to incoming calls are commonly dimensioned by *caller*. The cell values of these cubes represent the number of calls, the probability distributions, etc. Calling pattern cubes, several examples of which are described below, are derived from profile cubes and then rolled up.

Cube CB.o represents the outgoing calling behavior of a customer. In Oracle Express that is defined by the following: define CB.o variable int <sparse <duration time dow callee>> inplace.

Similarly, cube CB.d representing incoming calling behavior is defined by the following: define CB.d variable int <sparse <duration time dow caller>> inplace.

The cell values of these cubes are the number of calls falling into the given 'slot' of time, duration, day of week, etc. When generated, CB.o and CB.d are rolled up along dimensions *duration*, *time* and *dow*. Therefore, CB.o(duration 'short', time 'morning', dow 'MON') measures the number of short-duration calls this customer made to each callee (dimensioned by callee) on Monday mornings during the profiling interval. Similarly, CB.o(duration 'all', time 'allday', dow 'week') measures the number of calls this customer made to each callee (total calls dimensioned by callee) during the profiling interval.

## A Method for Deriving a Calling Pattern Cube

An exemplary method that can be utilized by the BPGM 158 to generate a calling pattern cube CB.o from a profile cube PC, defined above, will now be described. It is noted that other calling pattern cubes can be generated in a similar way.

Cube PC is pre-populated using the data retrieved from database table *Profile* and possibly combined with cube PCS that is generated from loading call data. With the following algorithm, the calling pattern cube, CB.o, is populated for a given customer as specified by parameter *customer\_callID*.

```
define genCB (customer_callID text)
{
  - if customer_callID is not a value of caller
    then return

  - remove old cells of CB.o by
    limit dimensions duration, time, dow and callee to all their values
    CB.o = NA
```

```

- limit dimensions duration, time, dow to their bottom level values
- limit dimension caller to the given customer by
5   limit caller to customer_callID
- limit dimension callee to those being called by the given customer, as
   limit callee to any(PC > 0, callee)
10  - form a subcube of PC by selecting only the data related to the given customer
   (the current value of caller dimension), then transfer (unravel) its cell values
   to cube CB.o, as
   CB.o = unravel(total(PC, duration time dow callee)
15  - rollup CB.o by
   limit duration, time, dow to all their values

   rollup CB.o over duration using dur_dur
   rollup CB.o over time using time_time
20  rollup CB.o over dow using dow_dow
}

```

### Behavior Profiling with Probability Distribution

For customer behavior profiling, the present invention first specifies which features (i.e., dimensions) are relevant. In one embodiment, in connection with calling behavior profiling, the present invention utilizes the following features for a customer's outgoing and incoming calls: the phone-numbers, volume (i.e., the number of calls), duration of the call, time of day the call was made, and day of week the call was made. Second, the present invention also specifies the granularity of each feature. For example, the time of day feature can be represented by the time-bins 'morning', 'afternoon', 'evening' or 'night'. Similarly, the duration feature can be represented by duration bins, such as 'short', 'medium', and 'long.' Each bin can be defined and set to predetermined values. In one embodiment, all calls that have a duration shorter than 20 minutes are placed into the 'short' bin. Also, all calls that have a duration between 20 minutes and 60 minutes are placed into the 'medium' bin, and all calls that have a duration longer than 60 minutes are placed into the 'long' bin. Third, the present invention specifies a profiling interval, which in a non-limiting example can be 3 months, and the periodicity of the profiles, which in a non-limiting example can be weekly. The profiling interval is that time interval over which the customer profiles are constructed, and the periodicity of the profiles is how often the customer profile is summarized. In this example, the customer's profile is a weekly summarization of his calling behavior during the profiling interval.

Based on the profiled information, the present invention derives calling patterns of individual customers. The present invention can generate the following three kinds of calling

patterns. The first type of calling pattern is a fixed-value based calling pattern. A fixed-value based calling pattern represents a customer's calling behavior with fixed values showing his "average" behavior. TABLE 1 illustrates a profile with a simple, fixed values. This profile describes the calling pattern from a first telephone number to a second telephone number during "morning", "afternoon", and "evening" periods. On an average, calls are of a medium duration during the morning, of a short duration during the afternoon, and of a long duration during the evenings.

TABLE 1

Morning	Afternoon	Evening
Medium	Short	Long

The second type of calling pattern is a volume-value based calling pattern. A volume based calling pattern summarizes a customer's calling behavior by counting the number of calls of different duration in different time-bins. Referring to FIG. 4, a volume based calling profile 400 describes the calling pattern from a first telephone number to a second telephone number. During the profiling period in the mornings, there were 350 calls of a short duration, 100 calls of a medium duration, and 50 calls of a long duration. During the profiling period in the afternoons, there were 30 calls of a short duration, 40 calls of a medium duration, and 30 calls of a long duration. During the profiling period in the evenings, there were 80 calls of a short duration, 200 calls of a medium duration, and 120 calls of a long duration.

The third type of calling pattern is a probability distribution based calling pattern. A probability distribution based calling pattern represents a customer's calling behavior with probability distributions. TABLE 2 illustrates a profile with probability distribution values. Specifically, the profile describes the calling pattern or behavior from a first telephone number to a second telephone number in terms of probability values. For example, in the mornings, 10% of the calls were long, 20% of the calls were medium, and 70% of the calls were short. In the afternoons, 30% of the calls were long, 40% of the calls were medium, and 30% of the calls

were short. In the evenings, 30% of the calls were long, 50% of the calls were medium, and 20% of the calls were short.

TABLE 2

	Morning	Afternoon	Evening
Short	0.7	0.3	0.2
Medium	0.2	0.4	0.5
Long	0.1	0.3	0.3

5 TheVPCM 164 of the present invention uses volume-based calling patterns as an intermediate step to derive probability-based calling patterns. Preferably, the present invention uses the probability distribution based calling patterns for detecting fraud for several reasons. First, probability distribution based calling patterns provide more fine-grained representation of dynamic behavior than fixed value based ones. Second, probability distribution based calling patterns also allow calling patterns that correspond to different lengths of profiling interval to be compared. For the threshold based fraud detection application, a long duration call may be noticed before reaching an absolute threshold, and monitored closer and closer as the probability of fraud becomes higher and higher. Third, probability distribution based calling patterns also provide more details of individual behavior that are not seen in fixed-value based calling patterns.

#### Computing Probability Distribution based Calling Patterns using OLAP

20 The present invention represents profiles and calling patterns as cubes. A cube has a set of underlying *dimensions*, and each cell of the cube is identified by one value from each of these dimensions. The set of values of a dimension *D*, called the *domain* of *D*, may be limited (by the OLAP *limit* operation) to a subset. A sub-cube (slice or dice) can be derived from a cube *C* by dimensioning *C* by a subset of its dimensions, and/or by limiting the value sets of these dimensions.

25 As mentioned above, the profile of a customer can be a weekly summarization of his activities in the profiling period. In the preferred embodiment of the present invention, the

information for profiling multiple customers' calling behavior are grouped into a single profile cube with dimensions  $\langle \textit{duration}, \textit{time}, \textit{dow}, \textit{callee}, \textit{caller} \rangle$ , where *dow* stands for day\_of\_week (e.g. Monday,..., Sunday), *callee* and *caller* are calling and called phone numbers. The value of a cell in a profiling cube measures the volume (i.e., the number of calls) made in the corresponding duration-bin, time-bin in a day, and day of week during the profiling period. In this way a profile cube records multiple customers outgoing and incoming calls week by week. From such a multi-customer profile cube, the present invention derives or generates calling pattern cubes of individual customers. The calling pattern cubes of individual customers have similar dimensions to the profile cubes except that a calling pattern cube for outgoing calls is not dimensioned by *caller*, and a calling pattern cube for incoming calls is not dimensioned by *callee* because they pertain to a single customer.

The size of each profile cube may be controlled by partitioning the customers represented in a profile cube by area and by limiting the profiling period. The present invention can generate multiple calling pattern cubes to represent a customer's calling behavior from different aspects. For example, some calling pattern cubes representing probability-based information can be derived from intermediate calling pattern cubes representing volume-based information.

FIG. 4 illustrates how calling pattern cubes representing probability-based information can be derived from intermediate calling pattern cubes representing volume-based information. A volume-based cube (V) 400 for a single customer is derived from the above profile cube by totaling outgoing calls over days of week. The volume cube (V) 400 holds the count of calls during the profiling period dimensioned by  $\langle \textit{time}, \textit{duration}, \textit{callee} \rangle$ , where dimension *time* has values 'morning', 'evening', etc.; *duration* has values 'short', 'long', etc.; and dimension *callee* contains the called phone numbers. A cell in the volume cube 400 is identified by one value from each of these dimensions. The value in a cell identified by *duration* = 'short', *time* = 'morning', and *callee* = '4089194444' is the number of calls made from this customer to '4089194444' in the mornings (e.g., from 8-12AM) that are 'short' (e.g., calls less than 20 minutes) during the profiling period.

Based on the volume cube 400, the VPCM 164 can generate, among other, the following different probability cubes:

- $C_{pri}$  410 for the prior probability of time-bin of calls with respect to each callee, that is dimensioned by  $\langle time, callee \rangle$ , and indicates the percentage of calls made in ‘morning’, ‘afternoon’, ‘evening’ and ‘night’, respectively.
- $C_p$  420 for the conditional probability of call duration-bin given time-bin of calls with respect to each callee, that is dimensioned by  $\langle time, duration, callee \rangle$ , indicates the percentage of calls that are ‘long’, ‘medium’ and ‘short’ respectively, given the time-bin.
- $C_{con}$  430 for the probabilistic consequence of the above (i.e., the probability of calls in every cell crossing) dimensioned by  $\langle time, duration, callee \rangle$  over the total calls.

It is noted that all the above probability cubes,  $C_{pri}$ ,  $C_p$ , and  $C_{con}$ , can be derived by the VPCM 164 based on the volume cube  $V$  by using OLAP operations. For example, in the Oracle Express OLAP language, these are expressed as

$$C_{pri} = total(V, time, callee) / total(V, callee)$$

$$C_p = (V / C_{pri}) / total(V, callee)$$

$$C_{con} = V / total(V, callee)$$

In the above expressions, *total* is an OLAP operation on cubes with numerical cell values. While *total(V)* returns the total of the cell values of  $V$ , *total(V, callee)* returns such a total dimensioned by *callee*, *total(V, time, callee)* returns such a total dimensioned by *time* and *callee*. In fact, a dimensioned *total* represents a cube. The arithmetic operations on cubes, such as ‘/’ used above, are computed cell-wise.

In view of the foregoing, the data management module 160 preferably makes only the volume cubes persistent data-warehouse objects since the probability cubes can be derived and generated based on the volume cubes. In the other words, only the volume-based information needs to be profiled by the profile builder and update module 154. Calling patterns, either based on volume or probability, can be derived by the customer behavior pattern generation module 158.

### Cubes Representing Probability Distribution based Calling Patterns

The Volume-based to Probability-based Conversion Module 164 derives or generates cubes representing probability distribution-based calling patterns from volume-based pattern cubes. For example, the Volume-based to Probability-based Conversion Module 164 can derive the following two kinds of such probability distribution-based pattern cubes: (1) “Probability

Distribution on All Calls” Cube, and (2) “Probability Distribution on Calls to Each Callee” Cube, which are described herein below. Although only two types of probability-based pattern cubes are described, it is noted that various other types of probability-based pattern cubes can be derived by the Volume-based to Probability-based Conversion Module 164 depending on the specific requirements of a particular application.

#### Probability Distribution on All Calls

Cube P\_CB.o for a customer represents the dimensioned probability distribution of outgoing calls over *all* the outgoing calls made by this customer, and can be derived from CB.o by the following:

```
define P_CB.o formula decimal <duration time dow callee>
EQ (CB.o/total(CB.o(duration 'all', 'allday', dow 'week')))
```

where total(CB.o(duration 'all', 'allday', dow 'week')) is the total calls this customer made to all callees. Since CB.o has already been rolled up, its top-level value can be utilized. The value of a cell is the above probability corresponding to the underlying dimension values.

#### Probability Distribution on Calls to Each Callee

Cube P1\_CB.o is dimensioned by duration, ... and callee, and represents the probability distribution of a customer's outgoing calls over his total calls to the corresponding callee, and is also derived from CB.o as specified by the following:

```
define P1_CB.o formula decimal <duration time dow callee>
EQ (CB.o/Total(CB.o(duration 'all', 'allday', dow 'week'), callee))
```

where total(CB.o(duration 'all', 'allday', dow 'week'), callee) is the total calls this customer made to each callee (dimensioned by callee). The value of a cell is the above probability corresponding to the underlying dimension values. Calling pattern cubes for incoming calls can be defined similarly.

#### Calling Pattern Similarity Comparison

The behavior pattern comparison module 168 compares the generated calling patterns with predetermined patterns to detect a match. This pattern comparison is important for many applications, such as caller fraud detection. Since the similarity of customer behavior can be represented from different angles, the present invention preferably compares calling patterns that

are derived from customer calling behavior profiles instead of comparing the profiles directly. For example, some calling patterns can be similar in the volume of calls to the same set of callees, while other calling patterns can be similar in the time of these calls, such as late night calls. Accordingly, the present invention provides an OLAP-based architecture for comparing  
5 calling patterns along multiple dimensions and at multiple levels in the dimension hierarchy.

It is noted that similarity of volume-based calling patterns is meaningful only when the patterns cover the same time span. In this regard, the present invention preferably measures the similarity of probability-based calling patterns so that patterns that cover different time spans can be compared meaningfully. For example, the present invention can be utilized to compare a predetermined calling pattern (e.g., a known fraudulent pattern) with an ongoing pattern in real-time.  
10

The foregoing description has provided examples of the present invention. One example has been directed to telecommunication fraud. It will be appreciated that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention as set forth in the appended claims. For example, the method of generating, updating, and comparing the customer profiles of the present invention can be applied to other areas, such as targeted marketing, targeted promotions, and general fraud detection. In applications where there is a very large collection of transaction data, the present invention can be utilized to generate customer behavior profiles, extract patterns of the activities of the customer, and  
15  
20 provide guidelines as to how to meet or otherwise service the needs of the customers.



What is claimed is:

1. A method for profiling customer behavior in a data processing system having a data warehouse and an OLAP server, the method comprising:
  - retrieving a plurality of records from the data warehouse;
  - generating a customer profile based on the records by utilizing OLAP programming; and
  - generating a customer behavior pattern based on the customer profile by utilizing OLAP programming.
2. A method as in claim 1 wherein said data warehouse has a call table and a profile table, wherein the step of generating a customer profile based on the records further comprises the steps of:
  - retrieving records from the call table and based thereon generating a snapshot cube representing the records, said snapshot cube having predetermined dimensions;
  - retrieving records from the profile table and based thereon generating a profile cube representing the records from the profile table, said profile cube having predetermined dimensions that are the same as the dimensions of the snapshot cube;
  - merging the snapshot cube and the profile cube to generate an updated profile cube; and
  - deriving a customer calling pattern based on the updated profile cube.
3. A method as in claim 2 further comprising:
  - comparing the customer calling pattern with a known fraudulent pattern,
  - if there is a match, then automatically generating an alert.
4. A method as in claim 1 further comprising:
  - analyzing the call pattern cube by utilizing at least one OLAP operation.

5. A method as in claim 4 wherein said OLAP operations is one of a roll-up operation, a drill-down operation, a dice operation, a slice operation, and an ad-hoc query.

6. A method as in claim 1 further comprising:

storing the updated profile cube into the profile table in the data warehouse.

7. A method as in claim 1 further comprising:

performing data staging between the profile table and the updated profile cube at predetermined time intervals.

8. A method as in claim 1 wherein said profile cube, snapshot cube, and updated profile cube each includes at least two dimensions and at least two levels.

9. A method as in claim 8 further comprising:

analyzing the call pattern cube by utilizing at least one OLAP operation along more than one level.

10. A method as in claim 8 further comprising:

analyzing the call pattern cube by utilizing at least one OLAP operation along more than one dimension.

11. A method as in claim 1 wherein the profile cube, snapshot cube, and the updated profile cube each are multi-level and multi-dimensional cubes.

12. A method as in claim 1 wherein the profile table and the call table each has a plurality of attributes, and the profile cube and snapshot cube each has a plurality of dimensions, said attributes corresponding in a one-to-one fashion to the dimensions.

13. A method as in claim 1 wherein the profile cube includes at least one cell having probability based values.

14. A data processing system comprising:  
a data warehouse for storing data in a relational format, said data warehouse including a profile table and a call table;  
an OLAP server, coupled to the data warehouse, for providing predetermined OLAP operations; and  
a profile engine, coupled to the data warehouse for generating a profile cube from information selected from the profile table, generating a snapshot cube, updating the profile cube by merging the profile cube and the snapshot cube to generate an updated profile cube, and deriving a calling pattern cube based on the updated profile cube.

15. A data processing system as in claim 14 further comprising:  
a fraud detection module for determining whether a reporting tool for use by a data analyst to generate a report having selected parameters based on the calling pattern cube.

16. A data processing system as in claim 14 further comprising:  
an analysis tool for use by a data analyst to compare the calling pattern cube to known fraudulent calling pattern cube.

17. A data processing system as in claim 14 further comprising:  
a visualization tool for use by a data analyst to display the calling pattern cube in different formats, levels, and dimensions.

2 18. A data processing system as in claim 14 further comprising:  
3 a data staging tool for transferring data between the profile cube stored in the OLAP  
4 server and profile table in the data warehouse at predetermined time intervals.  
5

1 19. A data processing system as in claim 14 further comprising:  
2 an analysis tool for use by a data analyst to extract information from calling pattern cube  
3 based on selected dimensions, levels, and ad-hoc queries provided by the data  
4 analyst.  
5

1 20. A method as in claim 1 further comprising:  
2 utilizing an OLAP server to create profiles, update profiles, derive calling patterns from  
3 the profiles, analyzing calling patterns, and comparing calling patterns;  
4 representing profiles and derived patterns as multi-dimensional and multi-level data  
5 cubes;  
6 utilizing an OLAP server as a scalable computation engine;  
7 representing customer profiles as volume cubes; and  
8 wherein the derived patterns are based on probability distributions, wherein patterns  
9 covering different intervals can be compared.

1 21. A method for generating customer profiles in a data processing system having a data  
2 warehouse and an OLAP server, said data warehouse having a call table, said method  
3 comprising:

4 representing customer profiles as profile data cubes;  
5 deriving pattern cubes from the profile data cubes utilizing OLAP operations; and  
6 analyzing the pattern cubes utilizing OLAP operations  
7

1 22. The method for generating customer profiles of claim 21 wherein the profile data cubes  
2 are multi-dimensional and multi-level cubes.  
3

24. The method for generating customer profiles of claim 21 wherein the profile data cube has a cell that includes a probability distribution value based on one of the probability distribution on calls to each callee and the probability distribution on all calls.

26. The method for generating customer profiles of claim 21 wherein the profile data cube represents a plurality of customers, and the pattern cube represents an individual customer.

## 10

Q




FIG. 1

100

**OLAP SERVER 108**

**OLAP TOOLS 150**

**OLAP-BASED PROFILE ENGINE 152**

**PROFILE BUILDER AND UPDATE MODULE  
(PBUM) 154**

**BEHAVIOR PATTERN GENERATION MODULE  
(BPGM) 158**

**DATA MANAGEMENT MODULE  
(DMM) 160**

**VOLUME-BASED TO PROBABILITY-BASED  
CONVERSION MODULE  
(VPCM) 164**

**BEHAVIOR PATTERN COMPARISON MODULE  
(BPCM) 168**

**FIG. 2**



FIG. 3

Cpri

morning	0.5
afternoon	0.1
evening	0.4

410

Cp

morning	afternoon	evening
short	0.7	0.3
medium	0.2	0.4
long	0.1	0.3
		0.3

Cp

420

Ccon

morning	afternoon	evening
short	0.35	0.03
medium	0.1	0.04
long	0.05	0.03
		0.12

Ccon

430

morning	afternoon	evening
short	350	30
medium	100	40
long	50	30
		120

V

400

FIG. 4

DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATIONATTORNEY DOCKET NO. 10991148-1

As a below named inventor, I hereby declare that:

My residence/post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**OLAP-Based Customer Behavior Profiling Method And System**

the specification of which is attached hereto unless the following box is checked:

( ) was filed on \_\_\_\_\_ as US Application Serial No. or PCT International Application Number \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understood the contents of the above-identified specification, including the claims, as amended by any amendment(s) referred to above. I acknowledge the duty to disclose all information which is material to patentability as defined in 37 CFR 1.56.

**Foreign Application(s) and/or Claim of Foreign Priority**

I hereby claim foreign priority benefits under Title 35, United States Code Section 119 of any foreign application(s) for patent or inventor(s) certificate listed below and have also identified below any foreign application for patent or inventor(s) certificate having a filing date before that of the application on which priority is claimed:

COUNTRY	APPLICATION NUMBER	DATE FILED	PRIORITY CLAIMED UNDER 35 U.S.C. 119
			YES <input type="checkbox"/> NO <input type="checkbox"/>
			YES <input type="checkbox"/> NO <input type="checkbox"/>

**Provisional Application**

I hereby claim the benefit under Title 35, United States Code Section 119(e) of any United States provisional application(s) listed below:

APPLICATION SERIAL NUMBER	FILING DATE

**U. S. Priority Claim**

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, Section 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

APPLICATION SERIAL NUMBER	FILING DATE	STATUS (patented/pending/abandoned)

**POWER OF ATTORNEY:**

As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

Customer Number **022879**Place Customer  
Number Bar Code  
Label hereSend Correspondence to:  
**HEWLETT-PACKARD COMPANY**  
Intellectual Property Administration  
P.O. Box 272400  
Fort Collins, Colorado 80528-9599**Direct Telephone Calls To:****Thomas X Li**  
**(650) 857-5972**

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Inventor: Qiming ChenCitizenship: CNResidence: 851 W. Remington Drive, Sunnyvale CA 94087Post Office Address: Same as ResidenceInventor's Signature Qiming ChenDate March 8, 2000

DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATION (continued)

ATTORNEY DOCKET NO. 10991148-1

Full Name of # 2 joint inventor: Umeshwar Dayal Citizenship: IN

Residence: 12561 Radoyka Drive, Saratoga CA 95070

Post Office Address: Same as residence

Umeshwar Dayal 8 March 2000  
Inventor's Signature Date

Full Name of # 3 joint inventor: Meichun Hsu Citizenship: US

Residence: 12717 Leander Drive, Los Altos Hills CA 94022

Post Office Address: Same as residence

Meichun Hsu Mar 8, 2000  
Inventor's Signature Date

Full Name of # 4 joint inventor: \_\_\_\_\_ Citizenship: \_\_\_\_\_

Residence: \_\_\_\_\_

Post Office Address: \_\_\_\_\_

\_\_\_\_\_  
Inventor's Signature Date

Full Name of # 5 joint inventor: \_\_\_\_\_ Citizenship: \_\_\_\_\_

Residence: \_\_\_\_\_

Post Office Address: \_\_\_\_\_

\_\_\_\_\_  
Inventor's Signature Date

Full Name of # 6 joint inventor: \_\_\_\_\_ Citizenship: \_\_\_\_\_

Residence: \_\_\_\_\_

Post Office Address: \_\_\_\_\_

\_\_\_\_\_  
Inventor's Signature Date

Full Name of # 7 joint inventor: \_\_\_\_\_ Citizenship: \_\_\_\_\_

Residence: \_\_\_\_\_

Post Office Address: \_\_\_\_\_

\_\_\_\_\_  
Inventor's Signature Date

Full Name of # 8 joint inventor: \_\_\_\_\_ Citizenship: \_\_\_\_\_

Residence: \_\_\_\_\_

Post Office Address: \_\_\_\_\_

\_\_\_\_\_  
Inventor's Signature Date